

Preliminary Amendment

Applicant: Alessandro Minzoni et al.

Serial No.: Unknown

(Priority Application No. DE 103 45 491.8)

(International Application No. PCT/EP2004/052126)

Filed: Herewith

(Priority Date: September 30, 2003)

(International Filing Date: September 10, 2004)

Docket No.: I438.111.101

Title: CLOCK RECEIVER CIRCUIT DEVICE, IN PARTICULAR FOR SEMI-CONDUCTOR COMPONENTS

REMARKS

This Preliminary Amendment amends the above identified Utility Patent Application filed herewith. With this Preliminary Amendment, claims 1-10 have been cancelled. Claims 11-31 have been added. Claims 11-31 remain pending in the application and are presented for consideration and allowance.

A substitute specification is included herewith. The specification contains no new matter

CONCLUSION

No fees are required under 37 C.F.R. 1.16(b)(c). However, if such fees are required, the Patent Office is hereby authorized to charge Deposit Account No. 50-0471.

The Examiner is invited to contact the Applicants' representative at the below-listed telephone number to facilitate prosecution of this application.

Preliminary Amendment

Applicant: Alessandro Minzoni et al.

Serial No.: Unknown

(Priority Application No. DE 103 45 491.8)

(International Application No. PCT/EP2004/052126)

Filed: Herewith

(Priority Date: September 30, 2003)

(International Filing Date: September 10, 2004)

Docket No.: 1438.111.101

Title: CLOCK RECEIVER CIRCUIT DEVICE, IN PARTICULAR FOR SEMI-CONDUCTOR COMPONENTS

Any inquiry regarding this Preliminary Amendment should be directed to Steven Dicke at Telephone No. (612) 573-2002, Facsimile No. (612) 573-2005. In addition, all correspondence should continue to be directed to the following address:

Dicke, Billig & Czaja
Fifth Street Towers, Suite 2250
100 South Fifth Street
Minneapolis, MN 55402

Respectfully submitted,

Alessandro Minzoni et al.,

By their attorneys,

DICKE, BILLIG & CZAJA, PLLC
Fifth Street Towers, Suite 2250
100 South Fifth Street
Minneapolis, MN 55402
Telephone: (612) 573-2002
Facsimile: (612) 573-2005

Date: March 30, 2006

SED:dmw

Steven E. Dicke

Steven E. Dicke

Reg. No. 38,431

CERTIFICATE UNDER 37 C.F.R. 1.10:

"Express Mail" mailing label number: EV309842324US

Date of Deposit: March 30, 2006

The undersigned hereby certifies that this paper or papers, as described herein, are being deposited in the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

By

Andrea Bullinger

Name: Andrea Bullinger

CLOCK RECEIVER CIRCUIT DEVICE, IN PARTICULAR FOR SEMI- CONDUCTOR COMPONENTS

5

Field of the Invention

The invention relates to a receiver, in particular a clock receiver circuit device, in terms of the preamble of Claim 1, as well as a semi-conductor component with such a circuit device.

10

Background

So-called clock signals are used in semi-conductor components, in particular in memory components such as DRAMs (DRAM = Dynamic Random Access Memory and/or Dynamic Read/Write Memory) – for instance based on CMOS technology - for the chronological co-ordination of the processing and/or relaying of data.

15

In conventional semi-conductor components a single clock signal (i.e. a so-called single-ended clock signal) – present on a single line – is generally applied.

The data can then for instance be relayed during the ascending clock flank of the single-ended clock signal (or alternatively for instance in each case during the

20

descending single-ended clock flank).

In conventional technology in addition, so-called DDR components, in particular DDR-DRAMS (DDR-DRAM = Double Data Rate DRAMs and/or DRAMs with double data rate), are already known.

25

With DDR components two differential, conversely equal clock signals – present on two separate lines - are used instead of a single clock signal (“single-ended” clock signal) present on a single line.

30

Whenever for instance the first of the two clock signals changes its state from “high logic” (for instance from a high voltage level) to “low logic” (for instance to a low voltage level) the second clock signal – essentially simultaneously – changes its state from “low logic” to “high logic” (for instance from a low to a high voltage level).

Conversely, whenever for instance the first clock signal changes its state from “low logic” (for instance from a low voltage level) to “high logic” (for instance to a high voltage level) the second clock signal – again essentially simultaneously – changes its state from a “high logic” to “low logic” (for instance from a high to a low voltage level).

5 In DDR components data is usually relayed during both the ascending flank of the first clock signal as well as during the ascending flank of the second clock signal (and/or during the descending flank of the first clock signal as well as during the descending flank of the second clock signal).

This has the effect that in a DDR component the relaying of data takes place
10 more frequently and/or more quickly (in particular twice as frequently or twice as quickly) than with corresponding conventional components with a single and/or “single-ended” clock signal, i.e. the data rate is higher, in particular twice as high as that of corresponding conventional components.

DDR components comprise for instance two – external – clock connections at
15 which corresponding differential clock signals clk, bclk – generated by an external clock generator - can be applied and relayed – directly – to corresponding inputs of a clock receiver circuit device.

Conventional clock receiver circuit devices for instance comprise four transistors, for instance a first and a second p-channel field effect transistor (for instance two p-
20 channel MOSFETs) as well as a first and a second n-channel field effect transistor (for instance two n-channel MOSFETs).

The source of the first n-channel field effect transistor can be connected with a (DC or constant) current source – connected with the ground potential – via corresponding lines. In similar fashion the source of the second n-channel field effect
25 transistor can be connected via corresponding lines with the (DC) current source – connected with the ground potential.

In addition, the gate of the first n-channel field effect transistor of the clock receiver circuit device can for instance be connected with the above (first) input of the circuit (at which for instance the above – first – clock signal clk is present) and the gate
30 of the second n-channel field effect transistor for instance with the above (second) input

of the circuit (at which for instance the above second clock signal bclk, inverted in relation to the first clock signal clk, is present).

The drain of the first n-channel field effect transistor can be connected with the gate of the first and second p-channel field effect transistor via a corresponding line, and with the drain of the first p-channel field effect transistor, as well as – via a corresponding line - with a (first) output of the clock receiver circuit (at which a (first) output signal bout can be detected).

In corresponding fashion the drain of the second p-channel field effect transistor can be connected with the drain of the second p-channel field effect transistor, as well as - via a corresponding further line - with a (second) output of the clock receiver circuit (at which a (second) output signal out can be detected).

The source of the first and second p-channel field effect transistor can in each case be connected with the corresponding supply voltage vddq.

The first output signal bout emitted by the clock receiver circuit device corresponds with the signal bclk present at the (second) input of the clock receiver circuit device, and the second output signal out, emitted by the clock receiver circuit device, with the signal clk present at the (first) input of the clock receiver circuit device (whereby – depending on the nature of the change of the input signals clk and/or bclk (for instance from "high logic" to "low logic", or vice versa) – the delay periods caused by the clock receiver circuit device can differ relatively strongly).

The output signals out, bout emitted by the clock receiver circuit device can be relayed to further circuits provided in the semi-conductor component, where they can for instance be used for the chronological co-ordination of the processing and/or relaying of data, i.e. as differential clock signals out, bout.

Summary

The present invention is aimed at making available provides a novel receiver, in particular a clock receiver circuit device, as well as a semi-conductor component with such a circuit device.

~~It achieves these and other aims by means of the subject matter described in claims 1 and 9.~~

~~Advantageous further developments of the invention are listed in the subsidiary claims.~~

In ~~terms of a basic concept~~ one embodiment of the invention a receiver, in particular a clock receiver circuit device is made available, with a first input adapted to be connected with a first connection of a semi-conductor component, and a second input adapted to be connected with a second connection of the semi-conductor component, characterized in that the receiver circuit device ~~comprises~~ includes several, in particular more than three, for instance four transfer gates.

Particularly advantageously transfer gates connected with one and the same output line are in each case controlled by differing, complementary input signals – present at the above inputs.

In this way it is achieved that each time a corresponding first transfer gate is switched “on”, a complementary second transfer gate allocated to this transfer gate – connected with the same output line - is switched “off”, (and vice versa), and correspondingly, that whenever a corresponding third transfer gate is switched “off”, a complementary fourth transfer gate allocated to this transfer gate – connected with the same output line – is switched “on” (and vice versa).

Brief Description of the Drawings

The accompanying drawings are included to provide a further understanding of the present invention and are incorporated in and constitute a part of this specification. The drawings illustrate the embodiments of the present invention and together with the description serve to explain the principles of the invention. Other embodiments of the present invention and many of the intended advantages of the present invention will be readily appreciated as they become better understood by reference to the following detailed description. The elements of the drawings are not necessarily to scale relative to each other. Like reference numerals designate corresponding similar parts.

Below the invention is more closely described by means of an embodiment example and the attached illustration. In the illustration:

Figure 1 ~~shows-illustrates~~ a schematic representation of a receiver, in particular a clock receiver circuit device in terms of an embodiment example of the present invention;

Figure 2 ~~shows-illustrates~~ a schematic representation of the chronological course of the input signals (clk; bclk) present at the clock receiver circuit device in terms of Figure 1, and of the signals (out; bout) emitted by the clock receiver circuit device, and

Figure 3 ~~shows-illustrates~~ a schematic representation of a receiver, in particular a clock receiver circuit device in terms of a further embodiment example of the present invention.

~~Clock receiver circuit device, in particular for semi-conductor components.~~

Detailed Description

In the following Detailed Description, reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. In this regard, directional terminology, such as "top," "bottom," "front," "back," "leading," "trailing," etc., is used with reference to the orientation of the Figure(s) being described. Because components of embodiments of the present invention can be positioned in a number of different orientations, the directional terminology is used for purposes of illustration and is in no way limiting. It is to be understood that other embodiments may be utilized and structural or logical changes may be made without departing from the scope of the present invention. The following detailed description, therefore, is not to be taken in a limiting sense, and the scope of the present invention is defined by the appended claims.

~~The invention relates to a receiver, in particular a clock receiver circuit device in terms of the preamble of Claim 1, as well as a semi-conductor component with such a circuit device.~~

~~So-called clock signals are used in semi-conductor components, in particular in memory components such as DRAMs (DRAM = Dynamic Random Access Memory~~

~~and/or Dynamic Read/Write Memory) — for instance based on CMOS technology — for the chronological co-ordination of the processing and/or relaying of data.~~

5 ~~In conventional semi-conductor components a single clock signal (i.e. a so-called single-ended clock signal) — present on a single line — is generally applied.~~

~~The data can then for instance be relayed during the ascending clock flank of the single-ended clock signal (or alternatively for instance in each case during the descending single-ended clock flank).~~

10 ~~In conventional technology in addition, so-called DDR components, in particular DDR-DRAMS (DDR-DRAM = Double Data Rate DRAMs and/or DRAMs with double data rate), are already known.~~

15 ~~With DDR components two differential, conversely equal clock signals — present on two separate lines — are used instead of a single clock signal (“single-ended” clock signal) present on a single line.~~

20 ~~Whenever for instance the first of the two clock signals changes its state from “high logic” (for instance from a high voltage level) to “low logic” (for instance to a low voltage level) the second clock signal — essentially simultaneously — changes its state from “low logic” to “high logic” (for instance from a low to a high voltage level).~~

25 ~~Conversely, whenever for instance the first clock signal changes its state from “low logic” (for instance from a low voltage level) to “high logic” (for instance to a high voltage level) the second clock signal — again essentially simultaneously — changes its state from a “high logic” to “low logic” (for instance from a high to a low voltage level).~~

30 ~~In DDR components data is usually relayed during both the ascending flank of the first clock signal as well as during the ascending flank of the second clock signal (and/or~~

during the descending flank of the first clock signal as well as during the descending flank of the second clock signal).

This has the effect that in a DDR component the relaying of data takes place more frequently and/or more quickly (in particular twice as frequently or twice as quickly) than with corresponding conventional components with a single and/or "single-ended" clock signal, i.e. the data rate is higher, in particular twice as high as that of corresponding conventional components.

DDR components comprise for instance two external clock connections at which corresponding differential clock signals *clk*, *belk* generated by an external clock generator can be applied and relayed directly to corresponding inputs of a clock receiver circuit device.

Conventional clock receiver circuit devices for instance comprise four transistors, for instance a first and a second p-channel field effect transistor (for instance two p-channel MOSFETs) as well as a first and a second n-channel field effect transistor (for instance two n-channel MOSFETs).

The source of the first n-channel field effect transistor can be connected with a (DC or constant) current source connected with the ground potential via corresponding lines. In similar fashion the source of the second n-channel field effect transistor can be connected via corresponding lines with the (DC) current source connected with the ground potential.

In addition, the gate of the first n-channel field effect transistor of the clock receiver circuit device can for instance be connected with the above (first) input of the circuit (at which for instance the above first clock signal *clk* is present) and the gate of the second n-channel field effect transistor for instance with the above (second) input of the circuit (at which for instance the above second clock signal *belk*, inverted in relation to the first clock signal *clk*, is present).

The drain of the first n-channel field effect transistor can be connected with the gate of the first and second p-channel field effect transistor via a corresponding line, and with the drain of the first p-channel field effect transistor, as well as via a
5 corresponding line with a (first) output of the clock receiver circuit (at which a (first) output signal out can be detected).

In corresponding fashion the drain of the second p-channel field effect transistor can be connected with the drain of the second p-channel field effect transistor, as well as
10 via a corresponding further line with a (second) output of the clock receiver circuit (at which a (second) output signal out can be detected).

The source of the first and second p-channel field effect transistor can in each case be connected with the corresponding supply voltage vddq.

The first output signal out emitted by the clock receiver circuit device corresponds with the signal belk present at the (second) input of the clock receiver circuit device, and the second output signal out, emitted by the clock receiver circuit device, with the signal clk present at the (first) input of the clock receiver circuit device
20 (whereby depending on the nature of the change of the input signals clk and/or belk (for instance from "high logic" to "low logic", or vice versa) the delay periods caused by the clock receiver circuit device can differ relatively strongly).

The output signals out, out emitted by the clock receiver circuit device can be
25 relayed to further circuits provided in the semi-conductor component, where they can for instance be used for the chronological co-ordination of the processing and/or relaying of data, i.e. as differential clock signals out, out.

The invention is aimed at making available a novel receiver, in particular a clock
30 receiver circuit device, as well as a semi-conductor component with such a circuit device.

It achieves these and other aims by means of the subject matter described in claims 1 and 9.

5 ~~Advantageous further developments of the invention are listed in the subsidiary claims.~~

10 ~~In terms of a basic concept of the invention a receiver, in particular a clock receiver circuit device is made available, with a first input adapted to be connected with a first connection of a semi-conductor component, and a second input adapted to be connected with a second connection of the semi-conductor component, characterized in that the receiver circuit device comprises several, in particular more than three, for instance four transfer gates.~~

15 ~~Particularly advantageously transfer gates connected with one and the same output line are in each case controlled by differing, complementary input signals—present at the above inputs.~~

20 ~~In this way it is achieved that each time a corresponding first transfer gate is switched “on”, a complementary second transfer gate allocated to this transfer gate—connected with the same output line—is switched “off”, (and vice versa), and correspondingly, that whenever a corresponding third transfer gate is switched “off”, a complementary fourth transfer gate allocated to this transfer gate—connected with the same output line—is switched “on” (and vice versa).~~

25

Below the invention is more closely described by means of an embodiment example and the attached illustration. In the illustration:

30 Figure 1—shows a schematic representation of a receiver, in particular a clock receiver circuit device in terms of an embodiment example of the present invention;

Figure 2 shows a schematic representation of the chronological course of the input signals (clk; belk) present at the clock receiver circuit device in terms of Figure 1, and of the signals (out; bout) emitted by the clock receiver circuit device, and

Figure 3 shows a schematic representation of a receiver, in particular a clock receiver circuit device in terms of a further embodiment example of the present invention.

In Figure 1 a schematic representation of a receiver, in particular a clock receiver circuit device in terms of an embodiment example of the present invention is shown.

The circuit device can for instance be installed into a semi-conductor component, for instance into a DRAM memory component (DRAM = Dynamic Random Access Memory and/or dynamic read/write memory) based on CMOS technology.

The DRAM memory component can for instance be a DDR DRAM (DDR DRAM = double data rate DRAM).

This component comprises two input clock connections 3a, 3b (for instance corresponding component pads connected with corresponding pins), whereby a first clock signal – generated by an external clock signal generator, i.e. of external origin – is applied to the first clock connection 3a, and a second clock signal bclk – similarly generated by the external clock signal generator – is applied to the second clock connection 3b.

The two clock signals clk and bclk may – as is for instance shown in Figure 2 - be differential, i.e. inversely equal clock signals; for instance whenever the first clock signal clk changes from a "high logic" to a "low logic" state, the second clock signal bclk – essentially simultaneously – changes its state from "low logic" to "high logic".

Conversely, whenever the first clock signal clk changes its state from "low logic" to "high logic" (in Figure 2 for instance at point t1) the second clock signal – essentially simultaneously (i.e. in Figure 2 for instance – also - at point t1) – changes its state from "high logic" to "low logic".

5

The above double data rate (in contrast to conventional components using only a single (single-ended) clock signal CLK) is achieved in the DDR component by respective data for instance not only being relayed during the ascending (or alternatively descending) clock flank of a single (single-ended) clock signal, but during the ascending flank of the first clock signal clk, as well as during the ascending flank of the second clock signal bclk (and/or both during the descending flank of the first clock signal clk as well as during the descending flank of the second clock signal bclk)(and/or during corresponding flanks of signals out, bout, and/or out', bout'(see below) derived from them)), i.e. twice as frequently than with conventional components with a single (single-ended) clock signal CLK.

15

As shown in Figure 1, the clock receiver circuit device 1 comprises four transfer gates and/or transmission gates 4, 5, 6, 7.

20

Each transfer gate 4, 5, 6, 7 in each case comprises – corresponding with conventional transfer gates – a (first) control input and a (second, inverse) control input.

25

The transfer gates 4, 5, 6, 7 can for instance – corresponding with conventional transfer gates – each comprise an n- and a p-channel MOSFET, whereby the gate of the n-channel MOSFET can for instance be connected with the first control input of each respective transfer gate 4, 5, 6, 7 and the gate of the p-channel MOSFET for instance with the second (inverse) control input of the respective transfer gates 4, 5, 6, 7 (or vice versa).

30

With the transfer gates 4, 5, 6, 7 in addition – corresponding with conventional transfer gates – the sources of the p- and of n-channel MOSFETs are in each case for

instance connected with each other and with a corresponding (first) transfer gate connection, and – correspondingly - for instance the drain of the n- and the drain of the p-channel MOSFETS are connected with each other and with a corresponding (second) transfer gate connection (or vice versa).

5

As is apparent from Figure 1, in the clock receiver circuit device 1, the clock connection 3a – where, as described above, the clock signal clk is present – is connected via a line 9a with the second (inverted) control input of the transfer gate 5 (the above – first – clock signal clk is thereby led to the second inverted control input of the transfer gate 5).

10

The line 9a is connected with via a line 9b connected with it, with a line 9c, which is connected with the first (non-inverted) control input of the transfer gate 7 (the above – first – clock signal clk is thereby – also - fed to the first non-inverted control input of transfer gate 7).

15

As is further apparent from Figure 1, in the clock receiver circuit device 1, the clock connection 3b – where, as described above, the second, inverted clock signal bclk is present – is connected with the second (inverted) control input of transfer gate 4 via line 8a (the above second clock signal bclk is thereby fed to the - second – inverted control input of the transfer gate 4).

20

Line 8a is connected, via a line 8b connected with it, with a line 8c, which is connected with the first non-inverted control input of transfer gate 6 (whereby the above second inverted clock signal bclk is – also – fed to the non-inverted control input of transfer gate 6).

25

In addition the line 8a - at which as described above, the second inverted clock signal bclk is present – is connected, via a line 8b connected with line 8a, with a line 8d, which is connected with a further line 8e, which is connected with the first (non-inverted) control input of transfer gate 5, and with the second, inverted control input of

30

transfer gate 7 (the above second, inverted clock signal bclk is thereby – also – fed to the first, non-inverted control input of transfer gate 5, and to the second, inverted control input of transfer gate 7).

5 As is further shown in Figure 1, the line 9a – where, as described above, the first clock signal clk is present – is connected via a line 9b connected with it, with a line 9d, which is connected with a further line 9e, which is connected with the second (inverted) control input of transfer gate 6 and with the first, non-inverted control input of transfer gate 4 (the above first clock signal clk is thereby – also – fed to the second, inverted control input of transfer gate 6 and to the first non-inverted control input of transfer gate 4).

15 In terms of Figure 1 the first (or the second) transfer gate connection of the transfer gate 4 is in each case connected – via a line 10a – with the – inverted – second (or first) transfer gate connection of transfer gate 5.

20 Correspondingly the first (or second) transfer gate connection of transfer gate 6 is in each case connected – via a line 10b – with the – inverted – second (or first) transfer gate connection of transfer gate 7.

25 Line 10b, at which the corresponding signal, emitted at the corresponding transfer gate connections of the transfer gates 6, 7 can be detected, is connected with an output line 11a, at which the first output signal of the clock receiver circuit device (first output signal out), corresponding with the first clock signal clk – as shown in Figure 2 described in more detail below – can be detected.

30 In corresponding fashion, line 10a, at which the corresponding signal emitted at the corresponding transfer gate connections of the transfer gates 4, 5 can be detected, is connected with a (further) output line 11b, at which the second output signal of the clock receiver circuit device (second output signal bout) corresponding with the second clock signal bclk – shown in Figure 2 and described in more detail below - can be detected.

As is further shown in Figure 1, the further (second (or first)) transfer gate connection of transfer gate 4 is connected – via a line 12 - with the supply voltage vddq (which can for instance amount to between 2.5 V and 3.5 V, in particular for instance 2.5 V or 2.9 V).

In addition the further – inverted – (first (or second)) transfer gate connection of transfer gate 5 is connected with ground potential.

Correspondingly similar to transfer gate 4, the further (second (or first)) transfer gate connection of transfer gate 6 is connected – via line 14 - with the above supply voltage vddq.

In addition – correspondingly similar to transfer gate 5 – at transfer gate 7 the further – inverted – (first (or second)) transfer gate connection is also connected with ground potential.

The voltage level of the first and second output signals out, bout (in each case in a "high logic" state) can for instance amount to half the voltage level of the above supply voltage vddq, for instance between 1.25 V and 1.75 V, in particular for instance 1.25 V or 1,45 V.

If for instance as is shown in Figure 2 during a first clock phase, i.e., here till a point t1 (and especially in the above alternative) a "low logic" first clock signal clk is present at the first clock connection 3a (and thereby also – via line 9c – at the first, non-inverted control input of transfer gate 7, – via line 9e – at the first, non-inverted control input of transfer gate 6, – via line 9e – at the second inverted control input of transfer gate 4, and – via line 9a – at the second inverted control input of the transfer gate 5 a corresponding "low logic" signal), and if – during the same clock phase – a "high logic" second clock signal bclk is present at the second clock connection 3b (and thereby also – via line 8e - at the second, inverted control input of transfer gate 7, - via line 8c – at the

second, inverted control input of transfer gate 6, - via line 8a – at the first, non-inverted control input of transfer gate 4, and – via line 8e – at the first non-inverted control input of transfer gate 5 a corresponding "high logic" signal), the transfer gate 4 is switched off (i.e. both the connections of transfer gate 4 – connected with line 12 and/or 10a - are – relatively highly resistively – electrically disconnected from each other), transfer gate 5 is switched on and/or through (i.e. both the transfer gate connections of transfer gate 5 – connected with line 10a and/or 13 – are – at a relatively low level of resistivity – electrically connected with each other), transfer gate 7 is switched off (i.e. both the connections of transfer gate 7 – connected with line 10b and/or 15 – are – relatively highly resistively – disconnected from each other), and transfer gate 6 is switched on and/or through (i.e. both the transfer gate connections of transfer gate 6 – connected with line 14 and/or 10b - are – at a relatively low level of resistivity – electrically connected with each other).

The output line 11b of the clock receiver circuit device 1 is thereby – at a relatively low level of resistivity - electrically connected with the ground potential present at line 13 and – relatively highly resistively – electrically disconnected from line 12, which is connected with the supply voltage vddq; the clock signal bout emitted onto output line 11b is thereby – corresponding with the second input signal bclk and as shown in Figure 2 – "high logic".

In addition, the output line 11a of the clock receiver circuit device 1 is – at a relatively low level of resistivity – electrically connected with the supply voltage vddq present on line 14, and – relatively highly resistively – electrically disconnected from line 15, which is connected with the ground potential; the clock signal out emitted onto output line 11a is thereby – corresponding with the first input signal clk and as shown in Figure 2 – "low logic".

If – as illustrated in Figure 2, for instance at the start of a second clock phase following on the first clock phase, i.e. here at a point t1 (and particularly in the above alternative) – the first clock signal clk present at the first clock signal connection 3a

changes its state to "high logic" (and the corresponding signal present at the first, non-inverted control input of transfer gate 7, at the first, non-inverted control input of transfer gate 6, at the second, inverted control input of transfer gate 4, at the second, inverted control input of transfer gate 5 changes its state to "high logic"), and if the second clock signal bclk present at the second clock connection 3b, changes its state – essentially simultaneously (here: at point t1) – to "low logic" (and thereby the corresponding signal present at the second, inverted control of transfer gate 7, at the second, inverted control input of transfer gate 6, at the first non-inverted control input of transfer gate 4 and at the first, non-inverted control input of transfer gate 5 also changes its state to "low logic" logic") transfer gate 4 is switched on and/or through (i.e. both transfer gate connections of transfer gate 4 – connected with line 10a and/or 13 – are – at relatively low resistivity – electrically connected with each other), transfer gate 5 is switched off (i.e. both transfer gate connections of transfer gate 5 – connected with line 10a and/or 13 - are – relatively highly resistively – electrically disconnected), transfer gate 7 is switched on and/or through (i.e. both transfer gate connections of transfer gate 6 – connected with line 10b and/or 15 – are electrically connected – at a relatively low level of resistivity – with each other), and transfer gate 6 is switched off (i.e. both transfer gate connections of transfer gate 6 – connected with line 14 and/or 10b are – relatively highly resistively – electrically disconnected from each other).

The output line 11b of the clock receiver circuit device 1 is thereby – relatively highly resistively – electrically disconnected from the ground potential present at line 13, and – at relatively low resistivity – electrically connected with line 12, which is connected with the supply voltage vddq; the clock signal bout emitted onto output line 11b thereby – corresponding with the second input clock signal bclk, and as shown in Figure 2, having had a particular switching delay period Δt imposed on it in relation to the clock signal bclk, at a point t2 – changes its state to "low logic".

In addition the output line 11a of the clock receiver circuit device 1 is thereby – at relatively high resistivity – electrically disconnected from the supply voltage vddq present at line 14, and – at relatively low resistivity – electrically connected with line 15,

which is connected with the ground potential; the clock signal out emitted onto output line 11a thereby – corresponding with the first input clock signal clk, and as shown in Figure 2, having had a particular switching delay period Δt (which essentially corresponds with the above switching delay period Δt of the clock signal bout) imposed in relation to the clock signal clk, at a point t2 (i.e. at essentially the same point t2 as clock signal bout) – changes its state to "high logic".

The output signals (differential clock signals out, bout) derived from the input clock signals clk, bclk emitted onto output lines 11a, 11b, can then be relayed to further circuits provided in the semi-conductor component, and there for instance be used for the chronological co-ordination of the processing and/or relaying of data.

In the (clock) receiver circuit device 1 shown in Figure 1, use is made of the fact that each of the transfer gates 4, 5, 6, 7, - between corresponding transfer gate connections – comprises a variably adjustable ohmic resistance, with a resistivity value that depends on the control signals present at the respective control inputs.

In an alternative embodiment example of the invention, shown in Figure 3, the output signals (differential clock signals out, bout) emitted onto the output lines 11a, 11b and derived from the input clock signals clk, bclk, can – in a clock receiver circuit device 1, correspondingly similarly constructed with the clock receiver circuit device shown in Figure 1 – be used to “boost” a circuit 2, which has been similarly constructed to conventional receiver, especially clock receiver circuit devices.

As is apparent from Figure 3, the clock receiver circuit device 1 shown there has been identically constructed to the clock receiver circuit device 1 shown in Figure 1, except that the first clock signal clk, present at the first clock connection 3a of the corresponding semi-conductor component, is led to the second, inverted control input of transfer gate 6 and the first, non-inverted control input of transfer gate 4 not via the lines 9d, 9e shown in Figure 1, but rather – to the control input of the transfer gate 4 – via a separate line 9d' – for instance also connected with line 9b – and - to the control input of

the transfer gate 6 – via a separate line 9d'' – for instance also connected with line 9b –, and that the second clock signal bclk, present at the second clock connection 3b of the corresponding semi-conductor component, is led to the first, non-inverted control input of transfer gate 5, and to the second inverted control input of transfer gate 7 not via lines 8d, 8e shown in Figure 1, but rather – to the control input of transfer gate 5 – via a separate line 8d' – for instance connected with line 8b – and - to the control input of transfer gate 7 - via a separate line 8d'' – for instance also connected with the line 8b.

In addition – corresponding with the embodiment example shown in Figure 1 – with the clock receiver circuit device 1 according to Figure 3, the first clock signal clk present at the first clock connection 3a, is (additionally) led to the second, inverted control input of the transfer gate 5 (in fact via line 9a), and (in fact via line 9a, and the lines 9b, 9c connected with it) to the first non-inverted control input of the transfer gate 7.

Furthermore – also corresponding with the embodiment example shown in Figure 1 – with the clock receiver circuit device 1 according to Figure 3, the second clock signal bclk present at the second clock connection 3b, is (additionally also) led to the second, inverted control input of the transfer gate 4 (in fact via line 8a), and (in fact via line 8a, and the lines 8b, 8c connected with it) to the first non-inverted control input of transfer gate 6.

As is apparent from Figure 3, the circuit 2 has been similarly constructed to the conventional clock receiver circuits, except that the inputs 11c, 11d of circuit 2 are not – as is commonly done – directly connected with the corresponding clock connections 3a, 3b of the semi-conductor component (for instance input 11c with the clock connection 3b (or 3a), and input 11d with clock connection 3a (or 3b)), but rather input 11c with the output line 11b of the clock receiver circuit device 1 (onto which, as described above, the (clock) signal bout, corresponding with the input clock signal bclk, is emitted by the clock receiver circuit device 1) and input 11d with output line 11a of the clock receiver

circuit device 1 (onto which, as described above, the (clock) signal out, corresponding with the input clock signal clk is emitted by the clock receiver circuit device 1).

The circuit 2 comprises – correspondingly similar with conventional clock receiver circuit devices – four transistors 104a, 104b, 105a, 105b, and in fact a first and a second p-channel field effect transistor 104a, 104b (here: two p-channel MOSFETs) as well as a first and a second n-channel field effect transistor 105a, 105b (here: two n-channel MOSFETs 105a, 105b).

The source of the first n-channel field effect transistor 105a is connected via a line 115a and a line 115c with a (DC and/or constant) current source 116, which is connected – via a line 117 – with the ground potential. In corresponding fashion the source of the n-channel field effect transistor 105b is also connected with the (DC and/or constant) current source 116 – connected with ground potential - via a line 115b and the above line 115c.

In addition the gate of the first n-channel field effect transistor 105a is connected with the above (first) input 11c of circuit 2 and the gate of the second n-channel field effect transistor 105b with the above (second) input 11d of circuit 2.

The drain of the first n-channel field effect transistor 105a is connected with the gate of the first and second p-channel field effect transistors 104a, 104b via a line 109, and

with the drain of the first p-channel field effect transistor 104a as well as – via a line 107a – with a (first) output of circuit 2 (at which a (first) output signal out' can be detected).

In corresponding fashion the drain of the second n-channel field effect transistor 105b is connected with the drain of the second p-channel field effect transistor 104a, as well as – via a line 107b – with a (second) output of circuit 2 (at which a (second) output signal out' can be detected).

The source of the first and second p-channel field effect transistors 104a, 104b is – via a line 110 – in each case connected with the above supply voltage vddq.

The first output signal bout' – emitted onto line 107a – of the circuit 2 corresponds with the signal out (and/or the signal bout) present at input 11d of circuit 2 and/or with the signal clk present at clock connection 3a (and/or the signal bclk present at clock connection 3b).

The second output signal out' – emitted onto line 107b – of circuit 2, corresponds with the signal bout present at input 11c of circuit 2 (and/or the signal out) and/or the signal bclk present at the clock connection 3b (and/or the signal clk present at the clock connection 3a).

The output signals out', bout', derived from the input clock signals clk, bclk and emitted onto lines 107a, 107b, can be relayed to further circuits provided in the semiconductor component and used there for the chronological coordination of the processing and/or relaying of data, i.e. as differential clock signals out', bout'.

— Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that a variety of alternate and/or equivalent implementations may be substituted for the specific embodiments shown and described without departing from the scope of the present invention. This application is intended to cover any adaptations or variations of the specific embodiments discussed herein. Therefore, it is intended that this invention be limited only by the claims and the equivalents thereof.

Patent claims

1. — A receiver, in particular a clock receiver circuit device (1) with a first input (9a) adapted to be connected with a first connection (3a) of a semi-conductor component, and
5 second input (8a) adapted to be connected with a second connection (3b) of the semi-conductor component;
characterized in that
the receiver circuit device (1) comprises several, in particular more than three transfer gates (4, 5, 6, 7).

10 2. — A receiver circuit device (1) according to Claim 1, which comprises four transfer gates (4, 5, 6, 7).

3. — A receiver circuit device (1) according to Claim 1 or 2, in which at a first transfer
15 gate (5) a corresponding first transfer gate control input is connected with the second input (8a) of the receiver circuit device (1), and a corresponding second transfer gate control input, inverse in relation to the first transfer gate control input, is connected with the first input (9a) of the receiver circuit device (1).

20 4. — A receiver circuit device (1) according to Claim 3, in which at a second transfer gate (4) — connected with the first transfer gate (5) — a corresponding first transfer gate control input is connected with the first input (9a) of the receiver circuit device (1), and a corresponding second transfer gate control input, inverse in relation to the first transfer gate control input is connected with the second input (8a) of the receiver circuit device
25 (1).

5. — A receiver circuit device (1) according to one of the preceding claims, in which at
a third transfer gate (7) a corresponding first transfer gate control input is connected with the first input (9a) of the receiver circuit device (1), and a corresponding second transfer
30 gate control input, inverse in relation to the first transfer gate control input is connected with the second input (8a) of the receiver circuit device (1).

6. — ~~A receiver circuit device (1) according to Claim 5, in which at a fourth transfer gate (6) — connected with third transfer gate (7) — a corresponding first transfer gate control input is connected with the second input (8a) of the receiver circuit device (1);~~
5 ~~and a corresponding second transfer gate control input, inverse in relation to the first transfer gate control input, is connected with first input (9a) of the receiver circuit device (1).~~

7. — ~~A receiver circuit device (1) according to one of the above claims, in which~~
10 ~~differential clock signals (clk, belk) are present at the first and second inputs (9a, 8a).~~

8. — ~~A receiver circuit device (1) according to one of the claims 4 to 7, in which the signal (bout) — detectable between the first and second transfer gates (4, 5) — and/or the signal (out) — detectable between the third and fourth transfer gates (7, 6) — is used to~~
15 ~~boost a clock relaying circuit (2).~~

9. — ~~A clock receiver circuit device (1) with a first clock input (9a) for receiving a first clock signal (clk), and a second clock input (8a) for receiving a second clock signal (belk), inversely equal to the first clock signal (clk)~~

20 ~~—whereby at a first transfer gate (5) a corresponding first transfer gate control connection is connected with the second clock input (8a) of the clock receiver circuit device (1), and a corresponding second transfer gate control connection, inverse in relation to the first transfer gate control connection, with the first clock input (9a) of the clock receiver circuit device (1);~~
25 ~~—and whereby at a second transfer gate (4) a corresponding first transfer gate control connection is connected with the first clock input (9a) of the clock receiver circuit device (1), and a corresponding second transfer gate control connection, inverse in relation to the first transfer gate control connection, with the second clock input (8a) of the clock receiver circuit device (1);~~

~~whereby corresponding further connections of the transfer gates 4, 5) are
connected with each other and are jointly connected with a clock output
(11b) for emitting a clock output signal (bout).~~

- 5 10. ~~A semi-conductor component with a receiver, in particular a clock receiver
circuit device (1) according to one of claims 1 to 9.~~

~~Abstract~~

~~Clock receiver circuit device, in particular for semi-conductor components.~~

- 5 ~~The invention relates to a semi-conductor component with a receiver, in particular a~~
~~clock receiver circuit device (1), as well as a receiver, in particular a clock receiver~~
~~circuit device (1), with a first input (9a) adapted to be connected with a first connection~~
~~(3a) of a semi-conductor component, and second input (8a) adapted to be connected with~~
~~a second connection (3b) of the semi-conductor component,~~
10 ~~characterized in that~~
~~the receiver circuit device (1) comprises several, in particular more than three transfer~~
~~gates (4, 5, 6, 7).~~

- 15 ~~Figure 1~~

Reference numbers

	1	Clock receiver circuit device
	2	Circuit
5	3a	Clock connection
	3b	Clock connection
	4	Transfer gate
	4	Transfer gate
	4	Transfer gate
10	4	Transfer gate
	8a	Line
	8b	Line
	8c	Line
	8d	Line
15	8d'	Line
	8d''	Line
	8e	Line
	9a	Line
	9b	Line
20	9c	Line
	9d	Line
	9d'	Line
	9d''	Line
	9e	Line
25	10a	Line
	10b	Line
	11a	Output line
	11b	Output line
	11c	Input
30	11d	Input
	12	Line

12Line
12Line
12Line
104a—Transistor
5 104b—Transistor
105a—Transistor
105b—Transistor
107a—Line
107b—Line
10 110Line
115a—Line
115b—Line
115c—Line
116Current source
15 116Line